

**AMENDMENTS TO THE CLAIMS**

1 (Currently amended). A real time, multiple path imaging system, comprising:  
an independent optical viewing device having at least one optical viewing path viewed through an eyepiece;

a beam splitter removably attached to said optical viewing device, wherein the beam splitter divides the at least one optical viewing path into a first and a second optical viewing paths;

an electronic video imaging device that receives an optical image from the second split beam path and converts the optical image into an electronic image signal, wherein the video imaging device is removably attached in alignment with the eyepiece without internal modification of the basic optical viewing device and adjustable to accommodate varying sizes of eyepieces;

a camera control unit coupled to said video imaging device for creating a real time video signal representing images in said second optical viewing path;

~~an encoder in said camera control unit, wherein said encoder adds source identifying information as a unique identification code to the electronic image signal with a video adder;~~

a transmitter coupled to the camera control unit for wireless transmission of the real time video signals;

a remote receiver to receive the real time video signal from the transmitter, wherein the receiver can distinguish between a plurality of video signals transmitted from a plurality of camera control units.

Application No. 09/171,018

2 (Previously amended). The imaging system of claim 1, wherein:

the eyepiece terminates at least one of said at least one optical viewing paths, said beam splitter being aligned with said eyepiece.

3 (Cancelled).

4 (Previously amended). The imaging system of claim 1, wherein:

said video signals are distinguishable from one another by data in an on screen display added to said respective video signals by said camera control unit.

5 (Previously amended). The imaging system of claim 1, wherein:

said video signals are distinguishable from one another by respective transmission carrier frequencies transmitted by said camera control unit.

Claims 6-12 (cancelled).

13 (Previously amended). The imaging system of claim 1, further comprising:

a viewing screen connected to the receiver and terminating said second split beam path, said viewing screen having a viewing surface on which said second split beam path is substantially centrally disposed.

Claim 14 and 15 (cancelled).

Application No. 09/171,018

16 (Original). The imaging system of claim 1, wherein:

said wireless transmission comprises a satellite link.

17. (Previously added). The imaging system of claim 1, wherein:

the optical viewing device comprises one of the following: a monocular, a binocular, or a periscope.

18. (Currently amended). The imaging system of claim 1, further comprising:

an encoder in the camera control unit to encode the electronic image signal, wherein the encoder adds source identifying information as a unique identification code to the electronic image signal with a video adder.

19. (Previously added). The system of claim 18, wherein:

the encoder adds the source identifying information with a video adder as an on-screen display for an output device.

20. (Previously added). The system of claim 18, wherein:

the encoder comprises a key pad for entering a unique identification code that is received by a key pad decoder which adds characters generated by the code to the electronic video signal through a video adder.

Application No. 09/171,018

21. (Previously added). The system of claim 1, further comprising:

a decoder in the receiver to decode the encoded electronic video signal, wherein the decoder and receiver supply a base band video signal to an output device.

22. (Previously added). The system of claim 1, wherein:

the beam splitter and the electronic video imaging device are mounted in a circular member having an inner ring that removably attaches to the eyepiece of the optical viewing device, wherein the ring is replaceable with alternate rings of varying diameter to accommodate varying diameters of alternate eyepieces.

23. (Previously added). A method for real time, multiple path imaging, comprising:

observing an image of a subject through an eyepiece of an optical viewing device;

directing the image through optical beam splitter that divides the image into first and second optical viewing paths;

receiving the second optical viewing path into a video camera that is removably attached in alignment with the eyepiece without internal modification of the basic optical viewing device, wherein the video camera member is adjustable to accommodate varying sizes of eyepieces and converts the optical image into an electronic image signal;

transmitting the electronic image signal to a camera control unit;

encoding the electronic image signal in the camera control unit with an encoder, wherein the encoder enters source identifying information as a unique identification code that is added to the electronic image signal as an onscreen display with a video adder;

Application No. 09/171,018

transmitting the electronic image signal and added source identifying information in real time through a wireless transmitter to a remote receiver;

distinguishing between a plurality of electronic image signals transmitted from a plurality of camera control units and received at the receiver.

24. (Previously added). The method of claim 23, wherein:

the first optical viewpath divided by the beam splitter is terminated by the eyepiece, said beam splitter being aligned with the eyepiece.

25. (Previously added). The method of claim 23, further comprising:

distinguishing a plurality of video signals received by the receiver from one another by data in an on screen display added to said respective video signals by the camera control unit.

26. (Previously added). The method of claim 23, further comprising:

distinguishing a plurality of video signals from one another by respective transmission carrier frequencies transmitted by said camera control unit.

27. (Previously added). The method of claim 23, wherein:

encoding the electronic image signal adds the source identifying information with a video adder as an on-screen display for an output device.

Application No. 09/171,018

28. (Previously added). The method of claim 23, wherein:

the electronic image signal is encoded by entering a unique identification code with a key pad which adds coded characters to the electronic video signal through a video adder.

29. (Previously added). The method of claim 23, further comprising:

decoding the encoded electronic video signal with a decoder in the receiver, wherein the decoder and receiver supply a base band video signal to an output device.

30. (Previously added). The method of claim 23, further comprising:

mounting the beam splitter and the electronic video imaging device in a circular member having an inner ring that removably attaches to the eyepiece of the optical viewing device, wherein the ring is replaceable with alternate rings of varying diameter to accommodate varying diameters of alternate eyepieces.